Technical Data Sheet

2/13/2015

Model: AE4440Y-AC3C

Product Description

Type:	Reciprocating
Application:	HBP/CBP - High/Commercial Back Pressure
Refrigerant:	R-134a
Voltage/Frequency:	100-115V ~ 60Hz 100V ~ 50Hz
Version:	N/A

Product Specifications

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	0
Weight Unit of Measure:	N/A
Displacement (cc):	10.33
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	285

Electrical

Voltage Range (50 Hz):	90-110
Voltage Range (60 Hz):	90-127
Locked Rotor Amps (LRA):	32.5
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	4.7
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	1.13
Motor Resistance (Ohm) - Start:	4.24
Motor Type:	CSR
Overload Type:	N/A
Relay Type:	N/A

Agency Approval

cURus Recognized